



Measuring and Modeling Shared Visual Attention

Jeffrey B. Mulligan

NASA Ames Research Center

Workshop on Computational and Mathematical Models in Vision
May 2016

My collaborator



Patrick Gontar
Institute of Ergonomics, TU
Munchen

Patrick's experiment




Simulated approach to
NYC/JFK with multiple
problems

Crews rated by instructor(s)

Objective measures: fuel
consumption, time
spent/remaining, etc.

High-level goals:


- determine what styles of
crew coordination
lead to successful
outcomes
- use results to inform




training

Haslbeck, A., Gontar, P. & Schubert, E. (2014). How Can Procedures and Checklists Help Pilots in Abnormal Flight Situations? In N. A. Stanton, S. J. Landry, G. Di Bucchianico & A. Vallicelli (Eds.), *Advances in Human Aspects of Transportation. Part II* (S. 456-461). AHFE International.

Eye gaze as a proxy for attention



vertical
speed






Format of the "raw" data


Index	UseCase	Area	StartFrame	StartTime	EndFrame	EndTime	Duration
1	Anfang - Ende	MCDU	334	00:00:13.360	340	00:00:13.600	00:00:00.240
2	Anfang - Ende	MCDU	811	00:00:32.440	844	00:00:33.760	00:00:01.320
3	Anfang - Ende	MCDU	848	00:00:33.920	867	00:00:34.680	00:00:00.760
4	Anfang - Ende	MCDU	891	00:00:35.640	925	00:00:37.000	00:00:01.360
5	Anfang - Ende	MCDU	967	00:00:38.680	975	00:00:39.000	00:00:00.320
6	Anfang - Ende	MCDU	986	00:00:39.440	1016	00:00:40.640	00:00:01.200
...							

Data sorted by "UseCase" (phase of flight) and "Area"

Converting the data back to a time series




A graphical representation



82 seconds

A graphical representation




21.8 minutes

Chi-square approach (thanks to A. Ahumada)



- Null hypothesis: observations drawn from same distribution
- Choose time window
- Convert from time series to fixation counts
(using average fixation duration)

Observed fixation durations



A 21 second example



	2F57	2C57	total	frac.	expected	
PFD	12	13	25	0.338	8.108	16.892
ATT	1	2	3	0.041	0.973	2.027
ALT	3	6	9	0.122	2.919	6.081
HDG	3	1	4	0.054	1.297	2.703
FMA	4	2	6	0.081	1.946	4.054
ND	0	22	22	0.297	7.135	14.865
SP	1	0	1	0.014	0.324	0.676
Wind	0	4	4	0.054	1.297	2.703
<hr/>						
total	24	50	74			

$$s = \sum_i \frac{(o_i - e_i)^2}{e_i} = 23.85$$

$$p = 0.0012$$



A Markov model of fixation sequences

- Probability of next state depends only on current state


$$P(s(t+1) = i \mid s(t) = j) = m_{ij}$$

$$P(s(t+2) = i \mid s(t) = j) = \sum_{k=1}^N m_{ik} m_{kj}$$

Example Markov models



M M² M³ M⁴ M⁵ M⁶




Synthetic data experiment details




- 10 randomly generated activities
- 2 sample records for each activity
- Compare statistics of matched/unmatched pairs


A scale-space image of Chi-squared p




A scale-space image of Chi-squared p




Histograms of p-values




Cumulative distributions of p-values




An ROC curve




AUC vs. scale




Between-activity correlations




AUC vs. scale




AUC vs. scale



Human data



Average of all crews





What to make of the human data?



- Very low p values at long time windows
- Suggests pilot and first officer average behaviors differ
- Suggests simple Markov model is a poor description



AUC vs. scale



Conclusions



- Chi-square statistics can be used to compare scan paths
- Results suggest that shared attention in the cockpit is limited to intervals < 1 minute
- Human activities in the cockpit are poorly described by random Markov processes
- Real activities are likely to involve small numbers of AOIs
- THANK YOU!